

TERUGSLAGKLEP



2 x binnendraad
staal verzinkt

WD bar	code	omschrijving	draad BSP	L mm	openings druk	max L / min	SW mm
400	90001780	ATR-1/4 0,5 bar	1/4"	60	0,5	25	19
400	90001783	ATR-3/8 0,5 bar	3/8"	70	0,5	40	24
350	90001786	ATR-1/2 0,5 bar	1/2"	78	0,5	80	30
300	90001789	ATR-3/4 0,5 bar	3/4"	94	0,5	110	36
270	90001792	ATR-1 0,5 bar	1"	106	0,5	140	45
250	90001795	ATR-1-1/4 0,5 bar	1-1/4"	123	0,5	200	55
200	90001798	ATR-1-1/2 0,5 bar	1-1/2"	138	0,5	300	65
400	90001781	ATR-1/4 4,0 bar	1/4"	60	4,0	25	19
400	90001784	ATR-3/8 4,0 bar	3/8"	70	4,0	40	24
350	90001787	ATR-1/2 4,0 bar	1/2"	78	4,0	80	30
300	90001790	ATR-3/4 4,0 bar	3/4"	94	4,0	110	36
270	90001793	ATR-1 4,0 bar	1"	106	4,0	140	45
250	90001796	ATR-1-1/4 4,0 bar	1-1/4"	123	4,0	200	55
200	90001799	ATR-1-1/2 4,0 bar	1-1/2"	138	4,0	300	65
400	90001782	ATR-1/4 8,0 bar	1/4"	60	8,0	25	19
400	90001785	ATR-3/8 8,0 bar	3/8"	70	8,0	40	24
350	90001788	ATR-1/2 8,0 bar	1/2"	78	8,0	80	30
300	90001791	ATR-3/4 8,0 bar	3/4"	94	8,0	110	36
270	90001794	ATR-1 8,0 bar	1"	106	8,0	140	45
250	90001797	ATR-1-1/4 8,0 bar	1-1/4"	123	8,0	200	55
200	90001800	ATR-1-1/2 8,0 bar	1-1/2"	138	8,0	300	65